




## Product Specification

AU OPTRONICS CORPORATION

(V ) Preliminary Specifications

( ) Final Specifications

Module	14.0" HD Color TFT-LCD with LED Backlight design
Model Name	B140XTN01.0 (H/W:0A)
Customer	Acer
Note (  )	LED Backlight with driving circuit design

Customer	Date
Checked & Approved by	Date
_____	_____
Note: This Specification is subject to change without notice.	

Approved by	Date
<u>Claire Yu</u>	<u>10/28/2011</u>
Prepared by	
<u>Yama Chen</u>	<u>10/28/2011</u>
NBBU Marketing Division / AU Optronics corporation	



# Product Specification

AU OPTRONICS CORPORATION

## Contents

<b>Preliminary spec .....</b>	<b>1</b>
<b>1. Handling Precautions .....</b>	<b>4</b>
<b>2. General Description .....</b>	<b>5</b>
2.1 General Specification .....	5
2.2 Optical Characteristics .....	6
<b>3. Functional Block Diagram .....</b>	<b>11</b>
<b>4. Absolute Maximum Ratings.....</b>	<b>12</b>
4.1 Absolute Ratings of TFT LCD Module .....	12
4.2 Absolute Ratings of Environment .....	12
<b>5. Electrical characteristics .....</b>	<b>13</b>
5.1 TFT LCD Module.....	13
5.2 Backlight Unit .....	18
<b>6. Signal Characteristic .....</b>	<b>19</b>
6.1 Pixel Format Image .....	19
6.3 Integration Interface and Pin Assignment.....	20
6.4 Interface Timing .....	23
6.5 Power ON/OFF Sequence .....	234
<b>7. Connector Description.....</b>	<b>26</b>
7.1 TFT LCD Module.....	26
<b>8. LED Driving Specification .....</b>	<b>27</b>
8.1 Connector Description.....	27
8.2 Pin Assignment.....	27
<b>9. Vibration and Shock Test .....</b>	<b>28</b>
9.1 Vibration Test .....	28
9.2 Shock Test Spec:.....	28
<b>10. Reliability.....</b>	<b>29</b>
<b>11. Mechanical Characteristics.....</b>	<b>30</b>
11.1 LCM Outline Dimension .....	30
11.2 Screw Hole Depth and Center Position .....	31
<b>12. Shipping and Package.....</b>	<b>32</b>
12.1 Shipping Label Format.....	32
12.2 Carton package .....	33
12.3 Shipping package of palletizing sequence.....	33
<b>13. Appendix: EDID description .....</b>	<b>34</b>



## Product Specification

AU OPTRONICS CORPORATION

### Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2011/07/29	All	Preliminary release		
0.2 2011/10/28	20	Update pin assignment	Update pin assignment	
	32	Update Z40 shipping label	Update Z40 shipping label	



## Product Specification

AU OPTRONICS CORPORATION

### 1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 13) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electronic breakdown.



## Product Specification

AU OPTRONICS CORPORATION

### 2. General Description

B140XTN01.0 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the HD (1366(H) x 768(V)) screen and 262k colors (RGB 6-bits data driver) with LED backlight driving circuit. All input signals are Display Port interface compatible.

B140XTN01.0 is designed for a display unit of notebook style personal computer and industrial machine.

### 2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	354.95 (14.0W")			
Active Area	[mm]	309.40 X 173.95			
Pixels H x V		1366x3(RGB) x 768			
Pixel Pitch	[mm]	0.2265X0.2265			
Pixel Format		R.G.B. Vertical Stripe			
Display Mode		Normally White			
White Luminance (ILED=20mA) (Note: ILED is LED current)	[cd/m <sup>2</sup> ]	200 typ. (5 points average) 170 min. (5 points average)			
Luminance Uniformity		1.25 max. (5 points)			
Contrast Ratio		500 typ			
Response Time	[ms]	8 typ / 16 Max			
Nominal Input Voltage VDD	[Volt]	+3.3 typ.			
Power Consumption	[Watt]	4.3 max. (Include Logic and Blu power)			
Weight	[Grams]	350 max.			
Physical Size <b>without inverter, bracket.</b>	[mm]		Min.	Typ.	Max.
		Length	323	323.5	324
		Width	191.5	192	192.5
		Thickness			5.2
Glass thickness	[mm]	0.5			
Electrical Interface		1 channel Display Port			
Surface Treatment		Glare, Hardness 3H,			
Support Color		262K colors ( RGB 6-bit )			



## Product Specification

AU OPTRONICS CORPORATION

Temperature Range		
Operating	[°C]	0 to +50
Storage (Non-Operating)	[°C]	-20 to +60
RoHS Compliance		RoHS Compliance

## 2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :


Item	Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance $I_{LED}=20mA$		5 points average	170	200	-	cd/m <sup>2</sup>	1, 4, 5.
Viewing Angle	$\theta_R$	Horizontal (Right) CR = 10 (Left)	40	45	-	degree	4, 9
	$\theta_L$		40	45	-		
	$\phi_H$	Vertical (Upper) CR = 10 (Lower)	10	15	-		
	$\phi_L$		30	35	-		
Luminance Uniformity	$\delta_{5P}$	5 Points	-	-	1.25		1, 3, 4
Luminance Uniformity	$\delta_{13P}$	13 Points	-	-	1.50		2, 3, 4
Contrast Ratio	CR		400	500	-		4, 6
Cross talk	%				4		4, 7
Response Time	$T_r$	Rising	-	-	-	msec	4, 8
	$T_f$	Falling	-	-	-		
	$T_{RT}$	Rising + Falling	-	8	16		
Color / Chromaticity Coordinates	Red	Rx	0.560	0.590	0.620	-	4
		Ry	0.315	0.345	0.375		
	Green	Gx	0.300	0.330	0.360		
		Gy	0.530	0.560	0.590		
	Blue	Bx	0.120	0.150	0.180		
		By	0.110	0.140	0.170		
	White	Wx	0.283	0.313	0.343		
		Wy	0.299	0.329	0.359		
			-	45	-		
NTSC	%						




# Product Specification

AU OPTRONICS CORPORATION

**Note 1:** 5 points position (Ref: Active area)



**Note 2:** 13 points position (Ref: Active area)



**Note 3:** The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance

$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

**Note 4:** Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting






## Product Specification

AU OPTRONICS CORPORATION

Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the center of screen.



**Note 5 :** Definition of Average Luminance of White ( $Y_L$ ):

Measure the luminance of gray level 63 at 5 points ,  $Y_L = [L(1) + L(2) + L(3) + L(4) + L(5)] / 5$

$L(x)$  is corresponding to the luminance of the point X at Figure in Note (1).

**Note 6 :** Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$

**Note 7 :** Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where

$Y_A$  = Luminance of measured location without gray level 0 pattern (cd/m<sup>2</sup>)


$Y_B$  = Luminance of measured location with gray level 0 pattern (cd/m<sup>2</sup>)






# Product Specification

AU OPTRONICS CORPORATION



**Note 8:** Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.






## Product Specification

AU OPTRONICS CORPORATION

### Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio  $\geq 10$ , at the screen center, over a  $180^\circ$  horizontal and  $180^\circ$  vertical range (off-normal viewing angles). The  $180^\circ$  viewing angle range is broken down as follows;  $90^\circ$  ( $\theta$ ) horizontal left and right and  $90^\circ$  ( $\phi$ ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.






## Product Specification

AU OPTRONICS CORPORATION

### 3. Functional Block Diagram

The following diagram shows the functional block of the 14.0 inches wide Color TFT/LCD 30 Pin (One CH/connector Module)





## Product Specification

AU OPTRONICS CORPORATION

### 4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

#### 4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	+4.0	[Volt]	Note 1,2

#### 4.2 Absolute Ratings of Environment


Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 4
Operation Humidity	HOP	5	95	[%RH]	Note 4
Storage Temperature	TST	-20	+60	[°C]	Note 4
Storage Humidity	HST	5	95	[%RH]	Note 4

Note 1: At Ta (25°C )

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: LED specification refer to section 5.2

**Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).**



Operating Range

Storage Range +



## Product Specification

AU OPTRONICS CORPORATION

### 5. Electrical characteristics

#### 5.1 TFT LCD Module

##### 5.1.1 Power Specification

Input power specifications are as follows;



The power specification are measured under 25°C and frame frequency under 60Hz

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	
PDD	VDD Power	-	1.2	1.5	[Watt]	Note 1/2
IDD	IDD Current	-	333	364	[mA]	Note 1/2
IRush	Inrush Current	-	-	2000	[mA]	Note 3
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	[mV] p-p	

Note 1 : Maximum Measurement Condition : Black Pattern

Note 2 : Typical Measurement Condition: Mosaic Pattern

Note 3 : Measure Condition



Vin rising time



## Product Specification


AU OPTRONICS CORPORATION

### 5.1.2 Signal Electrical Characteristics

Input signals shall be low or High-impedance state when VDD is off.

Signal electrical characteristics are as follows;

#### Display Port main link signal:



Display Port main link					
		Min	Typ	Max	unit
VCM	Differential common mode voltage	0.668	0.68	0.685	V
VDiff-P-P	Differential peak to peak voltage	0.1		1.32	V


Fallow as VESA display port standard V1.1a.



## Product Specification

AU OPTRONICS CORPORATION

### Display Port AUX\_CH signal:



Display Port AUX_CH					
		Min	Typ	Max	unit
VCM	Differential common mode voltage	0	$VDD/2$	0.15	V
VDiffP-P	Differential peak to peak voltage	0.4	0.6	0.9	V

Fallow as VESA display port standard V1.1a.

### Display Port VHPD signal:

Display Port VHPD					
		Min	Typ	Max	unit
VHPD	HPD voltage	2.25		3.6	V

Fallow as VESA display port standard V1.1a.






# Product Specification


AU OPTRONICS CORPORATION

## Display Port panel power sequence:



## Display port interface power up/down sequence, normal system operation

## Display Port AUX\_CH transaction only:



## Display port interface power up/down sequence, AUX\_CH transaction only



# Product Specification

AU OPTRONICS CORPORATION

## Display Port panel power sequence timing parameter:

Timing parameter	Description	Reqd. by	Limits			Notes
			Min.	Typ.	Max.	
T1	power rail rise time, 10% to 90%	source	0.5ms		10ms	
T2	delay from LCDVDD to black video generation	sink	0ms		200ms	prevents display noise until valid video data is received from the source
T3	delay from LCDVDD to HPD high	sink	0ms		200ms	sink AUX_CH must be operational upon HPD high.
T4	delay from HPD high to link training initialization	source				allows for source to read link capability and initialize.
T5	link training duration	source				dependant on source link to read training protocol.
T6	link idle	source				Min accounts for required BS-Idle pattern. Max allows for source frame synchronization.
T7	delay from valid video data from source to video on display	sink	0ms		50ms	max allows sink validate video data and timing.
T8	delay from valid video data from source to backlight enable	source				source must assure display video is stable.
T9	delay from backlight disable to end of valid video data	source				source must assure backlight is no longer illuminated.
T10	delay from end of valid video data from source to power off	source	0ms		500ms	
T11	power rail fall time, 90% to 10%	source			10ms	
T12	power off time	source	500ms			

1: The sink must include the ability to generate black video autonomously. The sink must automatically enable black video under the following conditions:

- upon LCDVDD power on (with in T2 max)-when the "Novideostream\_Flag" (VB-ID Bit 3) is received from the source (at the end of T9).
- when no main link data, or invalid video data, is received from the source. Black video must be displayed within 64ms (typ) from the start of either condition. Video data can be deemed invalid based on MSA and timing information, for example.

Note 2: The sink may implement the ability to disable the black video function, as described in Note 1, above, for system development and debugging purpose.

Note 3: The sink must support AUX\_CH polling by the source immediately following LCDVDD power on without causing damage to the sink device (the source can re-try if the sink is not ready). The sink must be able to respond to an AUX\_CH transaction with the time specified within T3 max.



## Product Specification

AU OPTRONICS CORPORATION

### 5.2 Backlight Unit

#### 5.2.1 LED characteristics

Parameter	Symbol	Min	Typ	Max	Units	Condition
Backlight Power Consumption	PLED	-	-	2.8	[Watt]	(Ta=25°C), Note 1 Vin =12V
LED Life-Time	N/A	10,000	-	-	Hour	(Ta=25°C), Note 2 If=20 mA

**Note 1:** Calculator value for reference  $P_{LED} = V_F$  (Normal Distribution) \*  $I_F$  (Normal Distribution) / Efficiency

**Note 2:** The LED life-time define as the estimated time to 50% degradation of initial luminous.

#### 5.2.2 Backlight input signal characteristics

Parameter	Symbol	Min	Typ	Max	Units	Remark
LED Power Supply	VLED	6.0	12.8	21.0	[Volt]	Define as Connector Interface (Ta=25°C)
LED Enable Input High Level	VLED_EN	2.5	-	5.5	[Volt]	
LED Enable Input Low Level		-	-	0.8	[Volt]	
PWM Logic Input High Level	VPWM_EN	2.5	-	5.0	[Volt]	
PWM Logic Input Low Level		-	-	0.8	[Volt]	
PWM Input Frequency	FPWM	200	800	1K	Hz	
PWM Duty Ratio	Duty	5	--	100	%	

## 6. Signal Characteristic

## 6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.

	1															1366														
1st Line	R	G	B	R	G	B	. . . . .															R	G	B	R	G	B			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.	.															.	.	.	.	.	.			
	.	.	.	.	.	.																								



## Product Specification

AU OPTRONICS CORPORATION

### 6.3 Integration Interface and Pin Assignment

**eDP lane** is a differential signal technology for LCD interface and high speed data transfer device.


PIN NO	Symbol	Function
1	NC	No Connect
2	H_GND	High Speed Ground
3	NC	
4	NC	
5	H_GND	High Speed Ground
6	Lane0_N	Comp Signal Link Lane 0
7	Lane0_P	True Signal Link Lane 0
8	H_GND	High Speed Ground
9	AUX_CH_P	True Signal Auxiliary Ch.
10	AUX_CH_N	Comp Signal Auxiliary Ch.
11	H_GND	High Speed Ground
12	LCD_VCC	LCD logic and driver power
13	LCD_VCC	LCD logic and driver power
14	NC	Reverse for AUO test only
15	LCD_GND	LCD logic and driver ground
16	LCD_GND	LCD logic and driver ground
17	HPD	HPD signal pin
18	BL_GND	Backlight_ground
19	BL_GND	Backlight_ground
20	BL_GND	Backlight_ground
21	BL_GND	Backlight_ground
22	BL_Enable	Backlight On / Off
23	BL_PWM_DIM	System PWM signal Input
24	NC	Reverse for AUO test only
25	NC	Reverse for AUO test only
26	BL_PWR	Backlight power (6V~21V)
27	BL_PWR	Backlight power (6V~21V)
28	BL_PWR	Backlight power (6V~21V)
29	BL_PWR	Backlight power (6V~21V)
30	NC	No Connect



# Product Specification

AU OPTRONICS CORPORATION

Note1: Start from right side






## Product Specification

AU OPTRONICS CORPORATION

Note2: Input signals shall be low or High-impedance state when VDD is off.  
internal circuit of **eDP inputs** are as following.







## Product Specification

AU OPTRONICS CORPORATION

### 6.4 Interface Timing


#### 6.4.1 Timing Characteristics

Basically, interface timings should match the 1366x768 /60Hz manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-	50	60	-	Hz
Clock frequency		1/ T <sub>Clock</sub>	-	69.3	-	MHz
Vertical Section	Period	T <sub>V</sub>	776	808	1023	T <sub>Line</sub>
	Active	T <sub>VD</sub>	768			
	Blanking	T <sub>VB</sub>	8	35	225	
Horizontal Section	Period	T <sub>H</sub>	1430	1606	1700	T <sub>Clock</sub>
	Active	T <sub>HD</sub>	1366			
	Blanking	T <sub>HB</sub>	64	240	334	

Note : DE mode only

#### 6.4.2 Timing diagram






## Product Specification

AU OPTRONICS CORPORATION

### 6.5 Power ON/OFF Sequence

VDD power on/off sequence is as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off




Parameter	Value			Units
	Min.	Typ.	Max.	
T1	0.5	-	10	(ms)
T2	10	-	-	(ms)
T3	30	40	50	(ms)
T4	210	-	-	(ms)
T5	10	-	-	(ms)
T6	0	-	-	(ms)
T7	110	-	-	(ms)
T8	0	16	50	(ms)
T9	>0 ( must exceed 0 )			(ms)
T10	-	-	10	(ms)
T11	1000	-	-	(ms)



## Product Specification

AU OPTRONICS CORPORATION

LED on/off sequence is as follows. Interface signals are also shown in the chart.



Symbol	Values			Unit
	Min	Typ	Max	
T1	10	---	---	ms
T2	10	---	---	
T3	50	---	---	
T4	0	---	---	
T5	10	---	---	



## Product Specification

AU OPTRONICS CORPORATION

### 7. Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

#### 7.1 TFT LCD Module

Connector Name / Designation	For Signal Connector
Manufacturer	IPEX
Type / Part Number	IPEX 20455-030E-02 or compatible
Mating Housing/Part Number	IPEX 20453-030T-01 or compatible



## Product Specification

AU OPTRONICS CORPORATION

### 8. LED Driving Specification

#### 8.1 Connector Description

It is a integrative interface and comibe into Display Port connector. The type and mating refer to section 7.

#### 8.2 Pin Assignment

Ref. to 6.3



## Product Specification

AU OPTRONICS CORPORATION

### 9. Vibration and Shock Test

#### 9.1 Vibration Test

**Test Spec:**

- Test method: Non-Operation
- Acceleration: 1.5 G
- Frequency: 10 - 500Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

#### 9.2 Shock Test Spec:

**Test Spec:**

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side



## Product Specification

AU OPTRONICS CORPORATION

### 10. Reliability

Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40°C, 90%RH, 300h	
High Temperature Operation	Ta= 50°C, Dry, 300h	
Low Temperature Operation	Ta= 0°C, 300h	
High Temperature Storage	Ta= 60°C, 300h	
Low Temperature Storage	Ta= -20°C, 250h	
Thermal Shock Test	Ta=-20°C to 60°C, Duration at 30 min, 100 cycles	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1

**Note1:** According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost  
. Self-recoverable. No hardware failures.

**Remark:** MTBF (Excluding the LED): 30,000 hours with a confidence level 90%






## Product Specification

AU OPTONICS CORPORATION

### 11. Mechanical Characteristics

#### 11.1 LCM Outline Dimension



Note: Prevention IC damage, IC positions not allowed any overlap over these areas.



## Product Specification


AU OPTRONICS CORPORATION

### 11.2 Screw Hole Depth and Center Position

Screw hole minimum depth, from side surface = 2.35 mm (See drawing)

Screw hole center location, from front surface =  $3.1 \pm 0.2$ mm (See drawing)

Screw Torque: Maximum 2.5 kgf-cm





## Product Specification

AU OPTRONICS CORPORATION

### 12. Shipping and Package

#### 12.1 Shipping Label Format

Size :90 mm(length) x35mm(width)

S01



Z40



Note : S01/Z40 is different from Module MFG




## Product Specification

AU OPTRONICS CORPORATION

### 12.2 Carton package

The outside dimension of carton is 454 (L)mm x 376 (W)mm x 302 (H)mm




### 12.3 Shipping package of palletizing sequence

The outside dimension of Pallet is 114(L)mm\* 83(W)mm\* 13.8(H)mm

By air : 6 \*4 layers, one pallet put 24 boxes, total 600 pcs module.

By sea : 6 \*6 layers, one pallet put 36 boxes, total 900 pcs module.





# Product Specification

AU OPTRONICS CORPORATION

## 13. Appendix: EDID description

### B140XTN01.0 EDID Code

Address	FUNCTION	Value	Value	Value
HEX		HEX	BIN	DEC
00	Header	00	00000000	0
01		FF	11111111	255
02		FF	11111111	255
03		FF	11111111	255
04		FF	11111111	255
05		FF	11111111	255
06		FF	11111111	255
07		00	00000000	0
08	EISA Manuf. Code LSB	06	00000110	6
09	Compressed ASCII	AF	10101111	175
0A	Product Code	3C	00111100	60
0B	hex, LSB first	10	00010000	16
0C	32-bit ser #	00	00000000	0
0D		00	00000000	0
0E		00	00000000	0
0F		00	00000000	0
10	Week of manufacture	00	00000000	0
11	Year of manufacture	15	00010101	21
12	EDID Structure Ver.	01	00000001	1
13	EDID revision #	04	00000100	4
14	<b>Video input def.</b> (digital I/P, non-TMDS, CRGB)	95	10010101	149
15	<b>Max H image size</b> (rounded to cm)	1F	00011111	31
16	<b>Max V image size</b> (rounded to cm)	11	00010001	17
17	<b>Display Gamma</b> $(=(gamma*100)-100)$	78	01111000	120
18	<b>Feature support</b> (no DPMS, Active OFF, RGB, tmg Blk#1)	02	00000010	2
19	Red/green low bits ( <b>Lower 2:2:2:2 bits</b> )	10	00010000	16
1A	Blue/white low bits ( <b>Lower 2:2:2:2 bits</b> )	B5	10110101	181
1B	Red x ( <b>Upper 8 bits</b> )	97	10010111	151
1C	Red y/ highER 8 bits	58	01011000	88
1D	Green x	57	01010111	87
1E	Green y	92	10010010	146
1F	Blue x	26	00100110	38
20	Blue y	1E	00011110	30
21	White x	50	01010000	80
22	White y	54	01010100	84



## Product Specification

AU OPTRONICS CORPORATION

23	Established timing 1	00	00000000	0
24	Established timing 2	00	00000000	0
25	Established timing 3	00	00000000	0
26	Standard timing #1	01	00000001	1
27		01	00000001	1
28	Standard timing #2	01	00000001	1
29		01	00000001	1
2A	Standard timing #3	01	00000001	1
2B		01	00000001	1
2C	Standard timing #4	01	00000001	1
2D		01	00000001	1
2E	Standard timing #5	01	00000001	1
2F		01	00000001	1
30	Standard timing #6	01	00000001	1
31		01	00000001	1
32	Standard timing #7	01	00000001	1
33		01	00000001	1
34	Standard timing #8	01	00000001	1
35		01	00000001	1
36	Pixel Clock/10000 LSB	12	00010010	18
37	Pixel Clock/10000 USB	1B	00011011	27
38	Horz active <b>Lower 8bits</b>	56	01010110	86
39	Horz blanking <b>Lower 8bits</b>	46	01000110	70
3A	HorzAct:HorzBlk <b>Upper 4:4 bits</b>	50	01010000	80
3B	Vertical Active <b>Lower 8bits</b>	00	00000000	0
3C	Vertical Blanking <b>Lower 8bits</b>	23	00100011	35
3D	Vert Act : Vertical Blanking <b>(upper 4:4 bit)</b>	30	00110000	48
3E	HorzSync. Offset	26	00100110	38
3F	HorzSync.Width	16	00010110	22
40	VertSync.Offset : VertSync.Width	36	00110110	54
41	Horz&Vert Sync Offset/Width <b>Upper 2bits</b>	00	00000000	0
42	Horizontal Image Size <b>Lower 8bits</b>	35	00110101	53
43	Vertical Image Size <b>Lower 8bits</b>	AD	10101101	173
44	Horizontal & Vertical Image Size <b>(upper 4:4 bits)</b>	10	00010000	16
45	Horizontal Border <i>(zero for internal LCD)</i>	00	00000000	0
46	Vertical Border <i>(zero for internal LCD)</i>	00	00000000	0
47	Signal <i>(non-intr, norm, no stero, sep sync, neg pol)</i>	18	00011000	24
48	Detailed timing/monitor	0C	00001100	12
49	descriptor #2	12	00010010	18



# Product Specification

AU OPTRONICS CORPORATION

4A		56	01010110	86
4B		46	01000110	70
4C		50	01010000	80
4D		00	00000000	0
4E		23	00100011	35
4F		30	00110000	48
50		26	00100110	38
51		16	00010110	22
52		36	00110110	54
53		00	00000000	0
54		35	00110101	53
55		AD	10101101	173
56		10	00010000	16
57		00	00000000	0
58		00	00000000	0
59		18	00011000	24
5A	Detailed timing/monitor	00	00000000	0
5B	descriptor #3	00	00000000	0
5C		00	00000000	0
5D		FE	11111110	254
5E		00	00000000	0
5F	Manufacture	41	01000001	65
60	Manufacture	55	01010101	85
61	Manufacture	4F	01001111	79
62		0A	00001010	10
63		20	00100000	32
64		20	00100000	32
65		20	00100000	32
66		20	00100000	32
67		20	00100000	32
68		20	00100000	32
69		20	00100000	32
6A		20	00100000	32
6B		20	00100000	32
6C	Detailed timing/monitor	00	00000000	0
6D	descriptor #4	00	00000000	0
6E		00	00000000	0
6F		FE	11111110	254
70		00	00000000	0





## Product Specification

AU OPTRONICS CORPORATION

71	Manufacture P/N	42	01000010	66
72	Manufacture P/N	31	00110001	49
73	Manufacture P/N	34	00110100	52
74	Manufacture P/N	30	00110000	48
75	Manufacture P/N	58	01011000	88
76	Manufacture P/N	54	01010100	84
77	Manufacture P/N	4E	01001110	78
78	Manufacture P/N	30	00110000	48
79	Manufacture P/N	31	00110001	49
7A	Manufacture P/N	2E	00101110	46
7B	Manufacture P/N	30	00110000	48
7C		20	00100000	32
7D		0A	00001010	10
7E	Extension Flag	00	00000000	0
7F	Checksum	91	10010001	145